

# OCEANMASTER

## OCEANMASTER

OceanMaster

GNSS

GNSS

IMU

IP68

GGA GSV GST GSA

### - OCEANMASTER

	DGPS	Fugro Marinestar®	IARTK	PPP	IAPPK	GNSS ( $\pm 60$ )
	0.5 - 2 m <sup>2</sup>	: 10 cm 95% : 15 cm 95%	: +/- (8 mm + 1 ppm x ) <sup>3</sup> : +/- (15 mm + 1 ppm x ) <sup>3</sup>	: < 0.1 m : < 0.2 m	: +/- (8 mm + 1 ppm x ) <sup>3</sup> : +/- (15 mm + 1 ppm x ) <sup>3</sup>	- 6 (DGPS) - 3 (RTK) - 2 (PPDGNSS) - 1 (IAPPK)
	0.02°	0.01°	0.01	< 0.01°	0.008°	0.03°
	0.01° 4 m	-	-	-	-	< 0.1°
	0.02° 2 m					( $\pm 60$ )
	5 cm 5% <sup>5</sup> 2 cm 2% <sup>6</sup>	-	-	-	-	5 cm 5% <sup>5</sup> 2 cm 2% <sup>6</sup>

### PC

	L = 442 mm, W = 356 mm, H = 46 mm	3.9 kg	-20 °C to +70 °C	10 - 80% RH	120/230 V, 50/60 Hz,
	L = 167 mm, W = 185 mm, H = 68 mm	2.5 kg	-20 °C to +60 °C	0- 100% RH	10-34 V, 35 W ( )

### IM

				IP
	L = 158 mm, W = 158 mm, H = 124 mm	2.5 kg	-40 °C to +60 °C	IP65
	Ø100 mm ( Ø132 mm) X 104 mm <sup>7</sup>	2.7 kg	-40 °C to +60 °C	IP68

### GN

GNSS	Ø178 mm, W = 73 mm	0.45 kg	-50 °C to +70 °C	0-100% RH
------	--------------------	---------	------------------	-----------

1  
2  
3 1 IMU-GNSS  
4  
5  
6  
7

1.

(10/100 base-T)

IMU            GNSS

(1Hz) UDP

TCP/IP

( 200 Hz) UDP

TCP/IP

2.